



DX5501TG

Wall-Mounted Digital Signage

Smart Display for Every
Visual Communication

55"



Product Feature

- Ultra HD display.
- Built-in information release system; support timer switch and local USB upgrade.
- Support various media formats such as images, videos, music, dynamic text, slideshows, interactive applications, dynamic forms, web pages, static text, APK applications, office files, etc.
- Support displaying channel logos, dates/times/weeks, weather forecasts, and real-time captions. Support background images and colors.
- A concise program publishing interface enables easy control over playback time, sequence, frequency, content, location, etc., ensuring well-organized programming.
- Intelligent scheduling supports various playback modes such as looping, timing, and spot insertions. Support timed and scheduled program releases, re-releases of historical programs, and automatic removal of expired programs, effectively reducing labor costs for remote content update and management. It also supports program import via USB drive or direct playback. Powerful multi-period timing power – on/off function enables unattended operation.
- Program preview with multi-level review ensures accurate information delivery, Support customized enterprise solutions and business expansion.
- Switch freely between horizontal and vertical orientations with smooth transitions and no black screen.





Specification	Model	Parameter
Panel	LCD Size	55"
	Panel Grade	A Grade
	Back Light Unit	LED
	Resolution	3840 x 2160pixels
	Brightness(typ)	300± 10cd/m ² (typ.)
	Contrast Ratio	1200:1
	Pixel Pitch	0.630×0.630 (H×V)
	Refreshing Frequency	60Hz
	Viewing Angle	178°(H/V)
	Life Time	50,000hrs(min.)
	Color Saturation	70%
	Display Area	1209.5 x 680.4 mm (H×V)
	Display Color	16.7M , 99% sRGB
Motherboard	Chip	GK6760-RBCFV100
	CPU	A55*8 (8 Core*A55)
	GPU	G52*4
	ROM/RAM	2+32GB
	Android	12.0
Touch System	Capacitive Touch	10 points touch
Power	Power Requirements	100-240V, 90-264V (Max.)~50/60Hz
	Max Power	≤110W
	Standby Power	< 0.5W
	Speaker Power	2 x 5W
	Power(AC) Input	100-240V
	Switch	Boat Switch





Specification	Model	Parameter
Environment Conditions	Operation Temperature	0°C~40°C
	Storage Temperature	-20°C~60°C
	Operation Humidity	10%~90% RH Non-Condensing
Onboard Interface	DC-12V INPUT (POWER IN)	1
	USB2.0-A	1
	USB3.0-A	1
	RJ45 Ethernet port (100M)	1
	HDMI IN2.0	1
	TF Card	1
	Line-Out	1
Physical Specifications	Net Weight	25.1±1kg
	Gross Weight	31.48±1kg
	Dimension	1250.8*721.4*55.8mm
	Packaging Dimension	1340*180*830mm
	Shell Material	Aluminum Frame+ Sheet Metal
	Color	Front frame (black) Back shell (black)
	Frame Width (T/B/L/R)	9.9/9.9/9.9/9.9
	VESA	400*400 4*M6 Wall-mounted screw
Language	OSD	English, Chinese, etc.
Accessories	Remote Control	1
	Power Cord	1(1.5M)
	Quick Start	1(A5 folded)
	Batteries	1(pair) (Export does not include)
	Wall Mount	1



Dimension



