



DX6501

Wall-Mounted Digital Signage

Smart Display for Every
Visual Communication

65"



Product Feature

- Ultra HD display.
- Built-in information release system; support timer switch and local USB upgrade.
- Support various media formats such as images, videos, music, dynamic text, slideshows, interactive applications, dynamic forms, web pages, static text, APK applications, office files, etc.
- Support displaying channel logos, dates/times/weeks, weather forecasts, and real-time captions. Support background images and colors.
- A concise program publishing interface enables easy control over playback time, sequence, frequency, content, location, etc., ensuring well-organized programming.
- Intelligent scheduling supports various playback modes such as looping, timing, and spot insertions. Support timed and scheduled program releases, re-releases of historical programs, and automatic removal of expired programs, effectively reducing labor costs for remote content update and management. It also supports program import via USB drive or direct playback. Powerful multi-period timing power – on/off function enables unattended operation.
- Program preview with multi-level review ensures accurate information delivery, Support customized enterprise solutions and business expansion.
- Switch freely between horizontal and vertical orientations with smooth transitions and no black screen.
- Remote terminal monitoring with real-time status checks, providing comprehensive business and management reports.
- Remote terminal system upgrade, intelligent DNS resolution and secure backup ensure convenient and efficient operation and maintenance.
- Supports WAN, LAN, Wi-Fi/4G network distribution, enabling cross-regional and inter-provincial multi-network networking (optional).





Specification	Model	Parameter
Panel	LCD Size	65"
	Panel Grade	A Grade
	Back Light Unit	LED
	Resolution	3840 x 2160pixels
	Brightness(typ)	500± 10cd/m²(typ.)
	Contrast Ratio	1100:1,1200:1,4000:1,5000:1(typ.)
	Pixel Pitch	0.372 (W) x 0.372(H)
	Refreashing Frequency	60Hz
	Viewing Angle	178°(H/V)
	Life Time	50,000hrs(min.)
	Color Saturation	70%
	Display Area	1432.28 (H)mm x 808.41(V)mm
	Display Color	1.07B (8-bit + Hi-FRC)
Motherboard	Chip	GK6760-RBCFV100
	CPU	A55*8 (8 Core*A55)
	GPU	G52*4
	ROM/RAM	2+32GB
	Android	12.0
Power	Power Requirements	100-240V, 90-264V (Max.)~50/60Hz
	Max Power	≤185W
	Standby Power	< 0.5W
	Speaker Power	2 x 5W(max)
	Power(AC) Input	100-240V
	Switch	Boat Switch





Specification	Model	Parameter
Environment Conditions	Operation Temperature	0°C ~ 40°C
	Storage Temperature	-20°C ~ 60°C
	Operation Humidity	10% ~ 90% RH Non-Condensing
Onboard Interface	DC-12V INPUT (POWER IN)	1
	USB2.0-A	1
	USB3.0-A	1
	RJ45 Ethernet port (100M)	1
	HDMI IN 2.0	1
	TF Card	1
	Line-Out	1
Physical Specifications	Net Weight	22.65 ± 1kg
	Gross Weight	34.1 ± 1kg
	Dimension	1446.08*822.21*64.3mm
	Packaging Dimension	1560*180*960mm
	Shell Material	Aluminum Frame+ Sheet Metal
	Color	Front frame (black) Back shell (black)
	Frame Width(T/B/L/R)	6.9/6.9/6.9/6.9
	VESA	400*400
Language	OSD	English, Chinese, etc.
Accessories	Remote Control	1
	Power Cord	1(1.5M)
	Quick Start	1(A5 folded)
	Batteries	1(pair)Export does not include
	Wall Mount	1



Dimension



1446.08mm

822.1mm



