



DX9800

Commercial Display Android

Next Generation Commercial
Display Solution

98"



The picture is for reference only

Product Feature

- Support for customizing the whole screen image when there is no signal from the machine.
- When there is a signal input, the signal source is intelligently identified, and the device can automatically switch to the corresponding channel without manual adjustment.
- Support Intel OPS module computer, through HDMI, USB and other data connections to achieve audio and video and data file communication.
- Support 4K Ultra HD display and full-channel 4K UI.
- Support wireless screen mirroring.
- Support Wi-Fi6, dual-band 2.4G/5G, AP+STA operation mode.
- Intelligent wake-up for HDMI/VGA/RS232 channel & network signal input in standby mode.
- Support for unified network sharing, both Android and OPS are gigabit networks.
- Support network sharing.





Specifications

Specification	Model	Parameter
Display	Size	98"
	Panel Grade	A Grade
	Back Light Unit	LED
	Resolution	3840 x 2160pixels
	Brightness(typ)	400cd/m ² (typ.)
	Contrast Ratio	1200:1 (typ.)
	Pixel Pitch	0.5622×0.5622mm (H×V)
	Refreshing Frequency	60Hz
	Viewing Angle	178°(H/V)
	Life Time	50,000hrs(min.)
	Color Saturation	69%
	Display Area	2158.85 (H)mm x 1214.35(V)mm
	Display Color	1.07B
Solution	Chip	T982-SR
	Android version	Android 13.0
	RAM	4GB
	ROM	32GB
Power	Power Requirements	Rated 100-240V, max 90-264V~50/60Hz
	Max Power	≤450W
	Standby Power	< 0.5W
	Speaker Power	2 x 10W(max)
	Power(AC) Input	100-240V
	Switch	Boat Switch



Environment

Environment	Operation Temperature	0°C ~ 40°C
	Storage Temperature	-20°C ~ 60°C
	Operation Humidity	10%~90% RH Non-Condensing
Input Interface	HDMI IN	2
	USB 3.0	2
	USB 2.0	1
	AUDIO IN	1
	RS232	1
	RJ45 IN	1
Output Interface	EARPHONE OUT	1
	TOUCH	1
	RJ45 OUT	1
OPS(Optional)	USB	USB2.0 x 2; USB3.0 x 2
	LAN INTERFACE	1
	HDMI OUT	1
	LINE-OUT	1
	MIC-IN	1
Wi-Fi	Version	802.11ac/b/g/n/a
	Operation Frequency	2.4GHz/5GHz



Bluetooth	Version	5.2
	Operation Frequency	2.4GHz
Physical Specifications	Net Weight	63±1kg
	Gross Weight	100±2kg
	Dimension L × W × T	2193.4*1255.3*90mm
	Dimension(package) L × T × H L × W × H	2525 x 435 x 1745mm(with pallet)
	Shell Material	Aluminum Frame+ Sheet Metal+ Aluminium composite panel
	Color	Front frame (black) Back shell (black)
	Frame Width (T/B/L/R)	15.9/20.1/15.9/15.9
	VESA	1000*400
Language	OSD	English, Chinese (Multi-Language)
Accessories	Remote Control	1
	Power Cord	1(1.5M)
	User Manual	1
	Quick Start	1(A5 folded)
	Batteries	1(pair)



dimension



Overall Dimension (W × H × D)	2193.4 × 1255.3 × 90 mm
Display Area (W × H)	2158.85 × 1214.35 mm
Package Dimension (L × W × H)	2525 × 435 × 1745 mm (with pallet)
VESA Mount	1000 × 400 mm
Net Weight	63 ± 1 kg
Gross Weight	100 ± 2 kg



