



GMZ01

— GATEWAY / HUB

Zigbee 3.0 · Ethernet

OPERATING VOLTAGE

5V DC

OPERATING CURRENT

1A

RATED POWER

5W

ava.com

ZIGBEE WIRED GATEWAY

Aluminium Alloy Smart Hub



OPERATING VOLTAGE	5V DC
OPERATING CURRENT	1A
RATED POWER	5W
WIRELESS PROTOCOL	Zigbee 3.0
PROTOCOL	Wi-Fi / Zigbee / Matter
COMMUNICATION	Ethernet + Zigbee
MAIN MODULE CHIP	RTL8196E
MAIN MODULE FIRMWARE	v1.23.2
ZIGBEE MODULE	TYZS4-IPEX
ZIGBEE FIRMWARE	v1.0.13

ZIGBEE CHIP	EFR32MG1B232F256GM48-C0
ANTENNA TYPE	PCB on-board + Built-in FPC
WIRELESS RANGE	≤ 20 m
OPERATING TEMP.	-20°C ~ 45°C
HUMIDITY	10%~90% RH (non-condensing)
ENCLOSURE MATERIAL	Aluminium alloy
NET WEIGHT	130 g
BOX DIMENSIONS	91 × 91 × 51 mm
CERTIFICATIONS	FCC / CE / RoHS